

RAMCO

HARD WORKER



BLOCK FIX **AAC**

HW302



FASTER AND STRONGER

★ **STRONG BOND**

★ **HIGH COVERAGE**

★ **EASY APPLICATION**

40KG

Why HW Block Fix AAC?

FASTER AND STRONGER

When speed matters and joints must stay perfectly aligned, HW Block Fix AAC gets the job done fast. With just a 3 mm layer, it cuts down on material, labour, and rework while delivering high bond strength for AAC and lightweight blocks. The smooth, self-curing mix flows easily, sets faster and leaves no hollow gaps.

STRONG BOND

Unlike regular cement-sand mortar, this dual polymer-modified adhesive grips instantly and holds AAC walls, with high adhesion strength.

HIGH COVERAGE

A thinner joint means less material. 40 – 50 kg covers 100 SQFT for 100 mm AAC Blocks – keeping movement, mixing, and waste to a minimum.

EASY APPLICATION

No curing. No soaking for blocks. Just add water, mix to a paste, and spread. The mix is smooth, and the finish stays clean.

ENGINEERED FOR AAC PERFORMANCE

The paste is tuned to match the size, porosity and surface texture of lightweight blocks - for a bond that holds firm without sag or shift.

BUILT FOR TOUGH SITES

Reduced shrinkage and cracking even with heat, rain or moisture movement across walls. Ideal for interior and exterior application in commercial and residential buildings, partitions and exteriors.

60
MINS

EXTENDED
POT LIFE

20
MINS

OPEN TIME FOR
PERFECT FINISH

READY FOR
PLASTERING IN

24
HRS

APPLICATION



Add HW to water.

10-11 L for 40 kg of HW302.



Mix to a thick paste.

Gradually mix with a slow speed blender.



Clean the blocks.



Apply 3 mm.

Use a notch trowel to spread consistently.



Fix the blocks.

Press firmly, use a rubber hammer.



Scan to watch Application Video.



Toll Free No: 1800 202 5700
customer@ramcocements.co.in